| The following standards are applicable to ROBAR products: | |
|---|--|
| ANSI B16.5 | Steel pipe flanges and flanged fittings. |
| ASTM A48 | Standard specifications for gray iron castings. |
| ASTM A536 | Standard specifications for ductile iron castings. |
| ASTM A743 | Standard specifications for castings. |
| ASTM A781 | Castings, steel and alloy, common requirements for general use. |
| ASTM D1330 | Specifications for rubber gaskets. |
| ASTM F593 | Stainless steel bolts, hex cap screws and studs. |
| ASTM F594 | Stainless steel nuts. |
| AWWA C111 | Rubber-gasket joints for ductile-iron pressure pipe and fittings. |
| AWWA C210 | Liquid epoxy coating systems for the interior and exterior of steel water pipelines. |
| AWWA C213 | Fusion bonded epoxy coating for the interior and exterior of steel water lines. |
| AWWA C219 | Bolted, sleeve-type couplings for plain-end pipes. |

Unless otherwise stated by Robar, all manufactured Robar products are rated for 150 PSI working pressure. Contact Robar for higher pressure ratings.



Only those products bearing the WQA mark are compliant.

ROBAR INDUSTRIES LTD.

Surrey, British Columbia Saint-Bruno, Quebec Phone: 1-800-663-6553 Phone: 1-800-315-9525

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com

Effective: January 1, 2015 **0.4.1**