



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 1180 ISOLATING BOOTS

USE

Robar 1180 Isolating Boot is used in conjunction with a standard Robar coupling to separate pipe ends in cathodically protected areas. Can also be used to increase the Odof an existing pipe by 1/4".

MATERIALS

Boot:

Gaskets are made from Styrene Butadiene Rubber (SBR) compound. Meets ASTM D2000 standard.
Other materials available on request.

PRESSURE

When following Robar installation instructions correctly the couplings will handle working pressures up to 175 PSI.
Contact Robar for higher working pressures.

SIZES AVAILABLE

4" - 24"

NOTE: End caps are required to be restrained either by a thrust block or a restrainer or else the force in the line will cause the coupling to slide off the pipe.

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com