



# ROBAR INDUSTRIES LTD.

## SUBMITTAL INFORMATION

### ROBAR 1606 STAINLESS STEEL COUPLING

**USE**

Robar 1606 couplings are used to make a non-restrained connection between pipes of the same diameter.

**MATERIALS**

Shell T-304 stainless steel

Gaskets Gaskets are made from Styrene Butadiene Rubber (SBR) compound. Meets ASTM D2000 standard.

Fasteners 5/8 inch diameter T-304 Stainless Steel. Nuts coated with anti-galling compound.

**PRESSURE**

When following Robar installation instructions correctly the couplings will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.

**SIZES AVAILABLE**

4" - 24" available. Contact Robar for larger sizes.

NOTE: Robar 1606 couplings do not meet AWWA C-219 standards.  
Couplings do not prevent pipe pull out

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: [www.robarindustries.com](http://www.robarindustries.com) / E-mail: [waterworks@robarindustries.com](mailto:waterworks@robarindustries.com)