



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 7800DJ/7900DJ SERIES FABRICATED DISMANTLING JOINT

USE Robar Dismantling Joints allows for adjustability once the flange and other fitting are in place. Dismantling Joints provide longitudinal adjustment which allows for future modifications or maintenance.

MATERIALS

Flange Body AWWA C-207 class D - ANSI 1021 150 lb drilling pattern.
Other classes of flanges available for higher pressures.

Fasteners 5/8 inch diameter. Meets AWWA C111 standards.
7808DJ/7508DJ - High Strength Low Alloy (HSLA) steel bolts and nuts.
7908DJ/7906DJ - T-304 Stainless Steel and heavy hex nuts. Nuts coated with anti-galling compound.
Tie Rods - ASTM A193 GR. B7, option Stainless steel

Coating 7808DJ/7906DJ - Two coats of enamel.
7908DJ/7906DJ - Fusion bonded epoxy coated per AWWA C-213 standard. Option AWWA C-210 Liquid Epoxy

Gaskets Gaskets are made from Nitrile Rubber (NBR) compound. Meets ASTM D2000 standard.
Other materials available on request.

PRESSURE When following Robar installation instructions correctly the Dismantling Joint will handle working pressures up to 150 PSI.
Contact Robar for higher working pressures.

SIZES AVAILABLE 14" - 96" available. Contact Robar for other sizes.

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com