



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

AWWA M-11 HARNESS RESTRAINT

USE

To restrain flexible couplings being installed on steel pipelines. The harnesses are supplied in half ring to allow for easy field welding.

MATERIALS

Restraint Rings

Two rings are required. One for each steel pipe on either side of the coupling. Rings are carbon steel per ASTM A193.

Tie Rods

Carbon Steel per ASTM A193 Gr B7. Stainless Steel rods available upon request. Twice as many rods are required.

Coating

Supplied bare unless otherwise requested.

PRESSURE

Per AWWA M11 manual, working pressures of 50 - 250 PSI are available. These pressures determine the quantity of tie rods and diameter of tie rods

SIZES AVAILABLE

6" - 96" for steel pipe. Larger sizes available on request.

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com