



# ROBAR INDUSTRIES LTD.

## SUBMITTAL INFORMATION

### ROBAR 2406/2506 CAST SERVICE SADDLE

<b><u>USE</u></b>	Robar 2406/2506 Service Saddles are used to take a service outlet off a transmission or distribution line.
<b><u>MATERIALS</u></b>	
Saddle Body	Cast Ductile Iron per ASTM A536 standard. Outlet thread are complaint with AWWA C-800-05
Gasket	Gaskets are made from Styrene Butadiene Rubber (SBR) compound. Meets ASTM D2000 standard. Other materials available on request.
Strap & Fasteners	5/8" NC T-304 Stainless Steel stud. 5/8" T-304 SS nuts coated with anti-galling compound. T-304 Stainless Steel strap - 14 gauge.
Coating	2406 - Two coats of red enamel 2506 - Fusion Bonded Epoxy per AWWA C-213 standard.
<b><u>PRESSURE</u></b>	When following Robar installation instructions correctly the saddle will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.
<b><u>SIZES AVAILABLE</u></b>	2" - 16" Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: [www.robarindustries.com](http://www.robarindustries.com) / E-mail: [waterworks@robarindustries.com](mailto:waterworks@robarindustries.com)