



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 2600 SERIES SERVICE SADDLE

USE

Robar 2600 series service saddle are used to take a service outlet off any transmission or distribution line.

MATERIALS

Saddle Body

T-304 Stainless Steel, fully passivated

Size 2" - 3" - 24 gauge

Size 4" - 8" - 20 gauge. Option of 18 gauge

Size 10" - 30" - 18 gauge

Outlet thread are complaint with AWWA C-800-05

Gasket

Gaskets are made from Styrene Butadiene Rubber (SBR) compound. Meets ASTM D2000 standard.

Other materials available on request.

Fasteners

5/8 inch diameter, T-304L Stainless Steel and heavy hex nuts. Nuts coated with anti-galling compound. Meets AWWA C111 standards.

PRESSURE

When following Robar installation instructions correctly the saddles will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

2" - 30" available. Contact Robar for larger sizes.

Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com