



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 2786 ISOLATING SADDLE

USE

Robar 2786 Service Saddles are used to take a service outlet off any transmission or distribution line. Primarily used in cathodically protected systems or to separate dissimilar metals.

MATERIALS

Saddle Body

Cast Bronze 85-5-5-5
Outlet thread are complaint with AWWA C-800-05

Gasket

Gaskets are made from Styrene Butadiene Rubber (SBR) compound. Meets ASTM D2000 standard.
Other materials available on request.

Fasteners

1/2" NC T-304 Stainless Steel.
1/2" T-304 SS nuts coated with anti-galling compound

Strap & Armor

4" wide 16 gauge T-304 Stainless Steel with RIC rubber.

PRESSURE

When following Robar installation instructions correctly the saddles will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

4" - 16" available.
Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com