



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 6636 SS ABANDON SERVICE SLEEVE

USE

Robar 6636 Abandon Service Sleeves are used to seal off abandoned or decommissioned 3/4" to 2" main stops. Allows for no disruption in water service. No re-chlorination required. Available in "Bolt Bracket" or "Lifter Bar" style.

MATERIALS

Shell T-304 Stainless Steel, fully passivated

Outlet Pipe T-304 Stainless Steel, fully passivated
& Cap Schd 10 SS pipe for branch

Side Bar, Armor T-304 Stainless Steel, fully passivated
& Fasteners 5/8" NC T-304 Stainless steel. Nuts coated with anti-galling compound

Gaskets Ring Seal - Nitrile (NBR)
Liner - Styrene Butadiene Rubber (SBR) compound. Meets ASTM D2000 standard. Other materials available.

PRESSURE

When following Robar installation instructions correctly the abandon sleeve will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

4" - 24"

Effective: 01/23/2015

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com