



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 1606 STAINLESS STEEL COUPLING

USE

Robar 1606 couplings are used to make a non-restrained connection between pipes of the same diameter.

MATERIALS

Shell

T-304 stainless steel

Gaskets

Gaskets are made from SBR (Buna S) compound. Meets ASTM D2000 standard.

Fasteners

5/8 inch diameter T-304 Stainless Steel. Nuts coated with anti-galling compound.

PRESSURE

When following Robar installation instructions correctly the couplings will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

4" - 24" available. Contact Robar for larger sizes.
Shell length available in 6" increments

NOTE: Robar 1606 couplings do not meet AWWA C-219 standards.
Couplings do not prevent pipe pull out

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com