

ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 6606 STAINLESS STEEL TAPPING SLEEVE

USE Robar 6600 series Tapping Sleeves are used for "WET" or "HOT" tap

applications to make a branch outlet off a main supply line. Can be

used on all types of pipe except for Concrete Cylinder Pipe.

Tapping Sleeves are available in "Lifter Bar" or "Bolt Bracket" style and have the option of having a SS flange, epoxy coated Carbon steel flange

or a MJ flange.

MATERIALS

Shell & T-304 Stainless Steel, fully passivated

Outlet Pipe Schd 10 SS, for size on size - 11 gauge pipe

Flange T-304 Stainless Steel as per AWWA C-228 class D

option - Epoxy Coated Carbon Steel, 150 lb

Option - MJ flange, stainless steel or carbon steel

Fasteners 5/8"NC T-304 Stainless Steel. Nuts coated with anti-galling compound.

Gaskets Ring Seal - Nitrile Rubber (NBR)

Liner - Nitrile Rubber (NBR) compound. Meets ASTM D2000 standard.

Other materials available.

Test Plug 3/4" NPT Stainless Steel

PRESSURE When following Robar installation instructions correctly the tapping

sleeves will handle working pressures up to 175 PSI. Contact Robar for

higher working pressures.

Meets applicable portions of AWWA C223

SIZES AVAILABLE 4" - 30" available. Contact Robar for larger diameters.

Effective: 06/01/2024

ROBAR IND LTD. - BRITISH COLUMBIA LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 604-591-8811 Phone: 450-441-7525
Toll Free: 800-663-6553 Toll Free: 800-315-9525
Fax: 604-591-5288 Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com