



# ROBAR INDUSTRIES LTD.

## SUBMITTAL INFORMATION

### ROBAR CAST DUCTILE TAPPING SLEEVE

#### USE

Robar 6506 Tapping Sleeves are used to make a branch outlet off a main supply line on Ductile or Cast Iron pipe only.

#### MATERIALS

Body &  
Flange

Cast Ductile Iron per ASTM A536 standard.  
Flange 150 pound bolt pattern

Fasteners

6504 - 3/4" NC Cast Ductile Carridge Bolts  
6506 - 3/4" NC T-304 Stainless Steel.

Coating

Waterarmor G17 Fusion Bonded Thermoplastic per AWWA C229 (Functionly conforms with AWWA C213).  
NSF/ANSI/CAN 61 approved.

Gaskets

Flange gaskets is O-Ring style. Gaskets are made from Nitrile Rubber (NBR) compound. Meets ASTM D2000 standard.

Test Plug

3/4" NPT Mild Steel

#### PRESSURE

When following Robar installation instructions correctly the tapping sleeve will handle working pressures up to 250 PSI. Contact Robar for higher working pressures.

#### SIZES AVAILABLE

4" - 8"

Effective: 06/01/2024

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: [www.robarindustries.com](http://www.robarindustries.com) / E-mail: [waterworks@robarindustries.com](mailto:waterworks@robarindustries.com)