



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 1410/1510 COUPLING END CAPS

USE

Robar 1410/1510 End Caps are used in conjunction with a standard Robar coupling for the purpose of capping ends of pipe.

MATERIALS

End Cap

The end caps are Cast Ductile Iron per ASTM A536 standards.

Plug

Ductile Iron - 2"IP square head

Coating

1410 - Two coats of enamel.
1510 - Fusion bonded epoxy coated per AWWA C213.

PRESSURE

When following Robar installation instructions correctly the couplings will handle working pressures up to 175 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

4" - 12"

NOTE: End caps are required to be restrained either by a thrust block or a restrainer or else the force in the line will cause the coupling to slide off the pipe.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com