



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 1908RSC RESTRAINED SLEEVE COUPLING

USE Robar 1908RSC Restrained Coupling are used to join plain end pipe with a flexible restrained connection. Suitable for PVC C-905, Ductile Iron and Cast Iron.

MATERIALS

Center Sleeve	Carbon Steel per ASTM A36
End Glands	EBAA 1100 Series for Ductile Iron Connections EBAA 2000 Series for C-905 connections
Gaskets	EBAA-Seal Mechanical Joint - SBR
Tie Rods/Fasteners	1908RSC - ASTM A193 Gr B7 Tie Rods 1906RSC - T-304 Stainless Steel Tie Rods
Coatings	Center Barrel - Fusion Bonded Epoxy per AWWA C-213 End Glands - EBAA Mega Bond

PRESSURE 14" - 16" Up to 350 PSI WP
18" - 48" Up to 250 PSI WP

SIZES AVAILABLE 14" - 48" available.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com