



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 2408/2508 CAST SERVICE SADDLE

USE

The Robar 2408/2508 service saddle is used to take a service outlet off a main transmission or distribution line.

MATERIALS

Saddle Body Cast Ductile Iron per ASTM A536 standard. Outlet thread are compliant with AWWA C-800-05

Gaskets Gaskets are made from Nitrile Butadiene Rubber (NBR) compound. Meets ASTM D2000 standard.
Other materials available on request.

Saddle Straps 5/8" NC Low Alloy Steel U-Bolt

Coating 2408 - Two coats of red enamel
2508 - Fusion Bonded Epoxy per AWWA C-213 standard.

PRESSURE

When following Robar installation instructions correctly the saddles will handle working pressures up to 350 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

4" - 16"
Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com