ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 2600 SERIES SERVICE SADDLE

USE

Robar 2600 series service saddle are used to take a service outlet off any transmission or distribution line.

MATERIALS

Saddle Body	T-304 Stainless Steel, fully passivated Size 2" - 3" - 24 gauge Size 4" - 8" - 20 gauge. Option of 18 gauge Size 10" - 30" - 18 gauge Outlet thread are compliant with AWWA C-800-05
Gasket	Gaskets are made from Nitrile Butadiene Rubber (NBR) compound. Meets ASTM D2000 standard. Other materials available on request.
Fasteners	5/8 inch diameter, T-304L Stainless Steel and heavy hex nuts. Nuts coated with anti-galling compound. Meets AWWA C111 standards.

PRESSURE

When following Robar installation instructions correctly the saddles will handle working pressures up to 250 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

2" - 30" available. Contact Robar for larger sizes.
Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA
Phone: 604-591-8811
Toll Free: 800-663-6553
Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC
Phone: 450-441-7525
Toll Free: 800-315-9525
Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com