



# ROBAR INDUSTRIES LTD.

## SUBMITTAL INFORMATION

### ROBAR 2996 CONCRETE CYLINDER SERVICE SADDLE

#### USE

Robar 2996 Service Saddles are used to take a service off concrete cylinder pipe. A grout opening is provided on the saddle body for restoring the concrete after tap is complete

#### MATERIALS

Saddle Body  
& Lugs

Cast Ductile Iron per ASTM A536 standard.

Gasket

Gaskets are made from Nitrile Rubber (NBR) compound.  
Meets ASTM D2000 standard.  
Other materials available on request.

Strap & Fasteners

5/8" NC T-304 Stainless Steel.  
5/8" T-304 SS nuts coated with anti-galling compound

Coating

Fusion Bonded epoxy coated per AWWA C-213 standard.

#### PRESSURE

When following Robar installation instructions correctly the saddle will handle working pressures up to 150 PSI. Contact Robar for higher working pressures.

#### SIZES AVAILABLE

16" - 36" available. Contact Robar for larger sizes.  
Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: [www.robarindustries.com](http://www.robarindustries.com) / E-mail: [waterworks@robarindustries.com](mailto:waterworks@robarindustries.com)