



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 6606 STAINLESS STEEL TAPPING SLEEVE

USE

Robar 6600 series Tapping Sleeves are used for "WET" or "HOT" tap applications to make a branch outlet off a main supply line. Can be used on all types of pipe except for Concrete Cylinder Pipe. Tapping Sleeves are available in "Lifter Bar" or "Bolt Bracket" style and have the option of having a SS flange, epoxy coated Carbon steel flange or a MJ flange.

MATERIALS

Shell & Outlet Pipe	T-304 Stainless Steel, fully passivated Schd 10 SS, for size on size - 11 gauge pipe
Flange	T-304 Stainless Steel as per AWWA C-228 class D option - Epoxy Coated Carbon Steel, 150 lb Option - MJ flange, stainless steel or carbon steel
Fasteners	5/8"NC T-304 Stainless Steel. Nuts coated with anti-galling compound.
Gaskets	Ring Seal - Nitrile Rubber (NBR) Liner - Nitrile Rubber (NBR) compound. Meets ASTM D2000 standard. Other materials available.
Test Plug	3/4" NPT Stainless Steel

PRESSURE

When following Robar installation instructions correctly the tapping sleeves will handle working pressures up to 175 PSI. Contact Robar for higher working pressures.

Meets applicable portions of AWWA C223

SIZES AVAILABLE

4" - 30" available. Contact Robar for larger diameters.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com