



# ROBAR INDUSTRIES LTD.

## SUBMITTAL INFORMATION

### ROBAR 6626 STAINLESS STEEL OUTLET SLEEVE

#### USE

Robar 6626 Outlet Sleeves are used for "DRY" tap (not pressurized) application. Particularly suited for use on High Density Polyethylene (HDPE) pipe.

#### MATERIALS

Shell &  
Outlet Pipe

T-304 Stainless Steel, fully passivated  
Schd 10 SS, for size on size - 11 gauge pipe

Flange

T-304 Stainless Steel as per AWWA C-228 class D  
(optional FIPT 304 SS outlets available)

Side Bar  
& Fasteners

T-304 Stainless Steel, fully passivated  
5/8" NC T-304 Stainless steel. Nuts coated with anti-galling  
compound

Gaskets

Ring Seal - Nitrile (NBR)  
Liner - Styrene Butadiene Rubber (SBR) compound. Meets  
ASTM D2000 standard.

#### PRESSURE

When following Robar installation instructions correctly the tapping sleeve will handle working pressures up to 175 PSI. Contact Robar for higher working pressures.

**Meets applicable portions of AWWA C223**

#### SIZES AVAILABLE

4" - 30" available. Contact Robar for larger diameters.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: [www.robarindustries.com](http://www.robarindustries.com) / E-mail: [waterworks@robarindustries.com](mailto:waterworks@robarindustries.com)