



6898 / 6996

CONCRETE CYLINDER PIPE TAPPING SLEEVE



SIZES AVAILABLE

16" to 120" Nominal Pipe OD on main supply line, 4" to 24" Nominal OD on branch line.

APPLICATIONS

ROBAR **6898** or **6996** Concrete Cylinder Pipe Tapping Sleeves complement our existing line of Tapping Sleeves. These fabricated sleeves are designed to reinforce the concrete cylinder pipe when the structural wires are cut and have the additional benefit of being able to be very easily installed.

STANDARD FEATURES

- Capable of working to 175 psi
- Oversized outlet for easy installation
- Broad gasket for sealing over weld areas
- Reinforced outlet seal face
- Installation of load bearing screws for valve support
- Shop coated over white metal cleaning
- 3 central grout holes
- Tapping valve location spigot

HOW TO ORDER

Determine the product number (**6898** or **6996**) and provide the following information:

1. OD of steel cylinder
2. OD/thickness of concrete
3. Outlet size
4. Line pressure
5. Line contents
6. Solid back or straps
7. Brand name of tapping valve used
8. Any unusual conditions or requirements

MATERIAL SPECIFICATIONS

Body:	Carbon Steel plate (ASTM A-36)
Flange:	Drilled and faced per ANSI standards Other drillings available. AWWA C207
Gaskets:	Nitrile (NBR) Rubber (AWWA C111)
Fasteners:	3/4" NC low alloy (AWWA C111)
Coating:	6898 Two coats of enamel
PSI Rating:	175 psi

OTHER CONFIGURATIONS

6996: Epoxy coated body, **T304** Stainless Steel fasteners

ROBAR INDUSTRIES LTD.

www.robarindustries.com
waterworks@robarindustries.com

Surrey, British Columbia
Phone: 1-800-663-6553

Saint-Bruno, Quebec
Phone: 1-800-315-9525