



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 6886/6996 CONCRETE CYLINDER TAPPING SLEEVE

USE

Robar 6886/6996 Concrete Cylinder Pipe Tapping Sleeve are used to make a branch outlet off a main supply line on Concrete Cylinder Pipe.

MATERIALS

Body

Carbon Steel per ASTM A36

Flange

Drilled and faced per ASTM or ANSI 150 lb standards.

Fasteners

6898/6998 - 3/4" NC HSLA Bolts & Nuts

6896/6996 - 3/4" NC T-304 Stainless Steel. Nuts coated with anti-galling compound.

Coating

6898/6998 - Two coats of enamel.

6998/6996 - Fusion bonded epoxy coated per AWWA C-213 standard.

Gaskets

Nitrile (NBR) rubber compound. Meets ASTM D2000 standard.

Other materials available on request.

PRESSURE

When following Robar installation instructions correctly the tapping sleeve will handle working pressures up to 175 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

16" - 48" available. Contact Robar for larger diameters.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com