



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 7906/7908RFCA RESTRAINED FLANGE COUPLING ADAPTER

USE

The Robar 7908RFCA Restrained Flange Coupling Adapter allows for a full restrained flexible joint to adapt from a flange to Ductile Iron Pipe or C-905 PVC Pipe.

MATERIALS

Center Sleeve	Carbon Steel per ASTM A36
Flange	AWWA C-207 class D - ANSI 1021 150 lb drilling pattern. Other classes of flanges available for higher pressures.
End Gland	EBAA 1100 Series for Ductile Iron Connections EBAA 2000 Series for C-905 connections
Gaskets	EBAA-Seal Mechanical Joint - SBR
Tie Rods/Fasteners	7908RSC - ASTM A193 Gr B7 Tie Rods 7906RSC - T-304 Stainless Steel Tie Rods
Coatings	Center Barrel - Fusion Bonded Epoxy per AWWA C-213 End Glands - EBAA Mega Bond

PRESSURE

14" - 16" Up to 350 PSI WP
18" - 54" Up to 250 PSI WP

SIZES AVAILABLE

14" - 54" available.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com